## WEVA RECTANGLE 6X3

Above-ground/ partially in-ground/ in-ground

Height 133 cm

## A straightforward, practical range; the accessible dream!

Structure made of class IV treated Northern pine, easy to install P-FI filtration system removable access ladder, double plank pine coping, 0.75 mm dark blue liner.



## STANDARD COMPLIANT EQUIPMENT

Every ProSwell pool complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- NF P90-316 | Private family pools pool kits general safety requirements and test methods.
- NF P90-317 | Private family pools means of access general safety requirements and test methods.
- NF P90-318 | Private family pools filtration groups and/ or filtration systems - general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).







Filter



ProSI



Wooden structure Pool fittings

by PRÖCOPI



27184210

Wooden pool Weva Rectangle 6x3 Double pine, Dark blue liner, Height: 133 cm







653 cm



Model	Rectangle 6x3
Supplier reference	27184210
EAN13	3566837096984
Outer dimensions (cm)	653 x 353 cm
Inner dimensions (cm)	600 x 300 cm
Height, coping included (cm)	133 cm
Water volume (m³)	21.78
Water surface area (m²)	18.00
Packaging	4 pallets

## **EQUIPMENT ITEMS AS STANDARD**



Ladder Pump





Wood structur Pool fittings Liner

Description	
Metallic structural braces	8
Made of class IV treated pine, thickness 28 mm and width 290 mm (2 x 145 mm).	included
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm	45
Liner thickness	0.75 mm
Liner colour	Dark blue
Number of skimmers, P-SM body	2
Number of return fittings	2
Buriable hydraulic fittings, Ø 45 mm	included

Description	
Sand filter	P-FS
Sand filter diameter (mm)	500 EH
Flow rate at the return fitting (m³/h)	9.70
Sand supplied (kg)	75
6-way valve (filtration/back wash/rinse/circulation/drain/closed)	included
1/4 turn valve, return and suction lines	included
In-pool SS ladder	3 treads
Wooden, safety, access ladder	4 treads
Underlay	included