

# TROPIC OCTO 414

Above-ground only

Height 120 cm

## A pool is not a luxury any more!

Structure made of class IV treated Northern pine, easy to install P-FI filtration system, removable access ladder, single plank pine coping, 0.50 mm dark blue liner.



## STANDARD COMPLIANT EQUIPMENT

Every ProSwell pool complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- **NF P90-316** | Private family pools - pool kits - general safety requirements and test methods.
- **NF P90-317** | Private family pools - means of access - general safety requirements and test methods.
- **NF P90-318** | Private family pools - filtration groups and/ or filtration systems - general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).



Ladder & pump



Liner



Filter



Wooden structure  
Pool fittings



27111205  
Wooden pool Tropic Octo 414  
Single pine, Dark blue liner, Height: 120 cm



Price  
incVAT





ProSwell  
by PROCOPI

# TROPIC OCTO 414

Above-ground only



## ASSEMBLY



Model	<b>Octo 414</b>
Supplier reference	<b>27111205</b>
EAN13	<b>3566837097264</b>
Outer dimensions (cm)	<b>414 cm</b>
Inner dimensions (cm)	<b>379 cm</b>
Height, coping included (cm)	<b>120 cm</b>
Water volume (m <sup>3</sup> )	<b>11.17</b>
Water surface area (m <sup>2</sup> )	<b>9.92</b>
Packaging	<b>2 pallets</b>

## EQUIPMENT ITEMS AS STANDARD



Description	
Single plank pine coping, thickness 28 mm, width 195 mm	<b>included</b>
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm	<b>45</b>
Liner thickness	<b>0.50 mm</b>
Liner colour	<b>Dark Blue</b>
Number of skimmers, P-SM body	<b>1</b>
Number of return fittings	<b>1</b>
Hydraulic connections, 38 mm not buriable	<b>included</b>

Description	
Sand filter	<b>P-FI</b>
Sand filter diameter (mm)	<b>400</b>
Flow rate at the return fitting (m <sup>3</sup> /h)	<b>5.20</b>
Sand provided (kg)	<b>25</b>
6 way valve (filtration/ back wash/ rinse/ circulation/ drain/ close)	<b>included</b>
In-pool SS ladder	<b>3 treads</b>
Wooden, safety, access ladder	<b>4 treads</b>
Underlay	<b>included</b>