

TROPIC OCTO 505

Above-ground only

Height 120 cm

A pool is not a luxury any more!

Structure made of class IV treated Northern pine, easy to install P-FI filtration system, removable access ladder, single plank pine coping, 0.50 mm dark blue liner.



STANDARD COMPLIANT EQUIPMENT

Every ProSwell pool complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- **NF P90-316** | Private family pools - pool kits - general safety requirements and test methods.
- **NF P90-317** | Private family pools - means of access - general safety requirements and test methods.
- **NF P90-318** | Private family pools - filtration groups and/ or filtration systems - general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).



Ladder & pump



Liner



Filter



Wooden structure
Pool fittings



27112205
Wooden pool Tropic Octo 505
Single pine, Dark blue liner, Height: 120 cm



ProSwell
by PROCOPI


Price
incVAT

TROPIC OCTO 505

Above-ground only



ASSEMBLY



Model	Octo 505
Supplier reference	27112205
EAN13	3566837097271
Outer dimensions (cm)	505 cm
Inner dimensions (cm)	470 cm
Height, coping included (cm)	120 cm
Water volume (m ³)	17.20
Water surface area (m ²)	15.64
Packaging	2 pallets

EQUIPMENT ITEMS AS STANDARD



Description	
Single plank pine coping, thickness 28 mm, width 195 mm	included
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm	45
Liner thickness	0.50 mm
Liner colour	Dark Blue
Number of skimmers, P-SM body	1
Number of return fittings	1
Hydraulic connections, 38 mm not buriable	included

Description	
Sand filter	P-FI
Sand filter diameter (mm)	400
Flow rate at the return fitting (m ³ /h)	5.20
Sand provided (kg)	25
6 way valve (filtration/ back wash/ rinse/ circulation/ drain/ close)	included
In-pool SS ladder	3 treads
Wooden, safety, access ladder	4 treads
Underlay	included