

TROPIC OCTO+ 510

Above-ground only

Height 120 cm

A pool is not a luxury any more!

Structure made of class IV treated Northern pine, easy to install P-FI filtration system, removable access ladder, single plank pine coping, 0.50 mm dark blue liner.



STANDARD COMPLIANT EQUIPMENT

Every ProSwell pool complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- **NF P90-316** | Private family pools - pool kits - general safety requirements and test methods.
- **NF P90-317** | Private family pools - means of access - general safety requirements and test methods.
- **NF P90-318** | Private family pools - filtration groups and/ or filtration systems - general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).



Ladder & pump



Liner



Filter



Wooden structure
Pool fittings



27113205

Wooden pool Tropic Octo+ 510

Single pine, Dark blue liner, Height: 120 cm



ProSwell
by PROCOPi

Price
incVAT





ASSEMBLY



Model	Octo+ 510
Supplier reference	27113205
EAN13	3566837113803
Outer dimensions (cm)	495 x 345 cm
Inner dimensions (cm)	439 x 309 cm
Height, coping included (cm)	120 cm
Water volume (m³)	14.14
Water surface area (m²)	12.85
Packaging	2 pallets

EQUIPMENT ITEMS AS STANDARD

GARANTIE 2 ans PROSWELL

Ladder Liner and Pump

GARANTIE 5 ans PROSWELL

Filter

GARANTIE 10 ans PROSWELL

Wood structure Pool fittings

Description		Description	
Single plank pine coping, thickness 28 mm, width 195 mm	included	Sand filter	P-FI
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm	45	Sand filter diameter (mm)	400
Liner thickness	0.50 mm	Flow rate at the return fitting (m³/h)	5.20
Liner colour	Dark Blue	Sand provided (kg)	25
Number of skimmers, P-SM body	1	6 way valve (filtration/ back wash/ rinse/ circulation/ drain/ close)	included
Number of return fittings	1	In-pool SS ladder	3 treads
Hydraulic connections, 38 mm not buriable	included	Wooden, safety, access ladder	4 treads
		Underlay	included