WEVA OCTO 530

Above-ground/ partially in-ground/ in-ground

Height 133 cm

A straightforward, practical range; the accessible dream!



STANDARD COMPLIANT EQUIPMENT

Every ProSwell pool complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- NF P90-316 | Private family pools pool kits general safety requirements and test methods.
- NF P90-317 | Private family pools means of access general safety requirements and test methods.
- NF P90-318 Private family pools filtration groups and/ or filtration systems - general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).



Wooden structure Pool fittings






27122210

Wooden pool Weva Octo 530 Double pine, Dark blue liner, Height: 133 cm






Above-ground/ partially in-ground/ in-ground

WEVA OCTO 530



Ø 528 cm



Model	Octo 530	
Supplier reference	27122210	
EAN13	3566837096830	
Outer dimensions (cm)	528 cm	
Inner dimensions (cm)	470 cm	
Height, coping included (cm)	133 cm	
Water volume (m ³)	18.77	
Water surface area (m ²)	15.64	
Packaging	2 pallets	

EQUIPMENT ITEMS AS STANDARD



5

Wood structure Pool fittings

Description	
Metallic structural braces	Not included
Made of class IV treated pine, thickness 28 mm and width 290 mm (2 x 145 mm).	included
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm	45
Liner thickness	0.75 mm
Liner colour	Dark blue
Number of skimmers, P-SM body	1
Number of return fittings	1
Buriable hydraulic fittings, Ø 45 mm	included
Sand filter	P-FI

Description	
Sand filter diameter (mm)	500
Flow rate at the return fitting (m ³ /h)	7.90
Sand supplied (kg)	50
6-way valve (filtration/back wash/rinse/circulation/drain/closed)	included
1/4 turn valve, return and suction lines	included
In-pool SS ladder	3 treads
Wooden, safety, access ladder	4 treads
Underlay	included