# TROPIC OCTO+ 540

Above-ground only

Height 120 cm

### A pool is not a luxury any more!

Structure made of class IV treated Northern pine, easy to install P-FI filtration system, removable access ladder, single plank pine coping, 0.50 mm dark blue liner.



#### STANDARD COMPLIANT EQUIPMENT

Every ProSwell pool complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- NF P90-316 | Private family pools pool kits general safety requirements and test methods.
- NF P90-317 | Private family pools means of access general safety requirements and test methods.
- NF P90-318 | Private family pools filtration groups and/ or filtration systems - general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).









Ladder & pump

Liner

Filter

Wooden structure Pool fittings

by PRÖCOPI






27115205 Wooden pool Tropic Octo+ 540 Single pine, Dark blue liner, Height: 120 cm



#### **ASSEMBLY**









Model

1110 0101		
Supplier reference	е	27115205
EAN13		3566837106843
Outer dimensions	s (cm)	523 x 313 cm
Inner dimensions	(cm)	487 x 277 cm
Height, coping in	cluded (cm)	120 cm
Water volume (m <sup>3</sup>	3)	13.43
Water surface are	ea (m²)	12.21
Packaging		2 pallets

## **EQUIPMENT ITEMS AS STANDARD**







Mood structure Pool fittings

Descriptif  Single plank pine coping, thickness 28 mm, width 195 mm  Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm  Liner thickness  Liner colour  Number of skimmers, P-SM body  Number of return fittings  Hydraulic connections, 38 mm  pot buriable  included	PROSWELL AND PROSWELL	PROSWELL	
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm  Liner thickness  Dark Blue  Number of skimmers, P-SM body  Number of return fittings  Hydraulic connections, 38 mm	Descriptif		
in mm, tolerance + or - 1 mm  Liner thickness  0.50 mm  Liner colour  Number of skimmers, P-SM body  Number of return fittings  Hydraulic connections, 38 mm	Single plank pine coping, thickness	included	
Liner colour  Dark Blue  Number of skimmers, P-SM body  Number of return fittings  Hydraulic connections, 38 mm  included	· '	45	
Number of skimmers, P-SM body  Number of return fittings  Hydraulic connections, 38 mm  Included	Liner thickness		0.50 mm
Number of return fittings 1 Hydraulic connections, 38 mm included	Liner colour		
Hydraulic connections, 38 mm	Number of skimmers, P-SM bod	У	1
included	Number of return fittings		1
Hot bullable	Hydraulic connections, 38 mm not buriable		included

Descriptif	
Sand filter	P-FI
Sand filter diameter (mm)	400
Flow rate at the return fitting (m³/h)	5.20
Sand provided (kg)	25
6 way valve (filtration/ back wash/ rinse/ circulation/ drain/ close)	included
In-pool SS ladder	3 treads
Wooden, safety, access ladder	4 treads
Underlay	included

Octo+ 540